





Parts Required:


Tools Used:

Step	Execution	Figures
1	Locate the front cross piece of the seat frame. Starting from under the chair seat, pass one end of the thigh belt between the second and third strap from the front of the seat	
2	For Pedal Rocker attachment, locate the front frame piece attached to the seat frame (resembles a handle)	
3	Pass the other end of the Thigh Belt through the same spot in the chair seat. Ensure that the center strap of the Thigh Belt is looped around the front cross piece of the seat frame	
4	One padded section of the Thigh Belt passes over each thigh. Connect the snap buckles behind the chair. Do not fasten around the cylinder or cable behind the chair. Tighten the straps as necessary	

5 Take the wing cover and slide it over top of the wing from the outside.



6 It should slide on tightly, and will wrap around the strap and the flap will Velcro shut on the inside portion of the wing.



7 Take the pad and clip the bottom buckles underneath the footplate portion of the footrest.




8 Take the straps and wrap them around the calf portion of the footrest and buckle.



9 Take the flap portion of the pad and slide it underneath the seat pad.



10 Take the straps with "D" rings and attach them around the seat frame and tighten.



- 11** Unbuckle attachment straps and position the shoulder bolster to the top of the wing



- 12** Attach the straps around the wing cover and secure with the buckles provided. Use the strap and "D" ring to secure the lower extended portion of the bolster to the back cane



For more information, please contact Broda Customer Care at 1-800-668-0637